Click here for firmware upgrade

You are now connected to your Nabaztag.

(You are NOT connected to the Internet. To reconnect to the Internet restart your Nabaztag.)

To configure your Rabbit, you will need the following information :

• Your SSID (the name of your network)

And if applicable :

- Your encryption type (WEP/WPA)
- Your wi-fi encryption key (WEP/WPA)
- Your authentication method (WEP)

5 Steps to connect your Nabaztag

- 1. Click on "click here to Start"
- 2. Enter the required information in the following page
- 3. When finished click on "Update and start"
- 4. Nabaztag will connect to the Internet : all four lights are going from ORANGE to GREEN
- 5. Reconnect to your usual wi-fi network and finish your registration.

Click here to Start

Basic configuration	
SSID	
TheCoolBaby - WPA-PSK encryption - Channel 11 - Power -3	Your wi-fi network should be in the list on the left.
OR type your network name :	If this is not the case, please type the name of your network in the field.
Encryption	
No encryption	
 WEP encryption WPA encryption 	Select your network's encryption type.
Кеу	
ouhouh les copines 2008	WEP : Key syntax is hexadecimal (10 or 26 chars) or ascii (5 or 13 chars) WPA : Key syntax can be any string
Update and Start	
	Advanced configuration

Advanced configuration (majority of users will not have to fill in this part)		
	Back to basic setup	
Authentication (WEP)		
OpenSystem	Select your authentication method.	
DHCP server		
DHCP enabled ? No	If your router gives IP addresses automatically to the peripherals on your network, leave this option on 'Yes'	
If you do not have DHCP server of	enabled, you do not need to fill in the following section	
Local IP		
192.168.1.253	Enter the static address assigned to your rabbit	
Local Mask		
255.255.255.0	Enter the mask assigned to your rabbit	
Local gateway		
192.168.1.1	Enter the gateway IP address assigned to your rabbit	
DNS Server		
80.10.246.2	Enter the IP address of the DNS assigned to your rabbit	
Proxy Server		
HTTP Proxy		
No	If you are accessing the Internet through a proxy, set this option to Yes and fill in the following fields	
Proxy IP address		
0.0.0.0	Enter the proxy IP address	
Proxy port		
0	Enter the port number used for the proxy	
	Update and Start	
General Info		
Serial number:	00:13:d3:86:2c:36	
Violet Platform:	193.149.120.33/vl	
Login:	00:00:00:00:00	
Firmware:	0.0.0.10	